



Specifications Sunrise IW60H Punch & Shear 60 Tonne Manufactured in Taiwan

#### Bar Shear

- Has adjustable hold down

#### Angle Shear

- Safety guarding around hold down
- Easily adjustable hold down
- Four cutting edges to all blades
- Mitre cut at 45 degrees

#### Flat Bar Shear

- Easily adjustable hold down
- Good visibility to blade line
- Table support with guides
- Angle flange trim/mitre to 45 degree
- Shaped blade to give minimum distortion

#### Features:

Punching capacity up to 40mm standard

Power inching for easy job set up

Adjustable stroke for faster punching

Punch table and shear table both fitted with guides as standard

All work stations guarded

Most cutting blades are four-sided for long life

Adjustable length stop with rule

Five work stations including notcher

Fully filtered hydraulic system

Internal & external mitre cutting of angle iron

Punching Diameter x Thickness (mm)	28 x 15, 40 x 11
Punching Throat Depth (mm)	220
Punching Maximum Stroke Length (mm)	55
Punching Work Table Height (mm)	1000
Flat Bar Shear (W x Thickness) MS (mm)	350 x 15, 210 x 20
Flat Bar Shear – Blade Length – MS (mm)	360
Flat Bar Shear Work Table Height (mm)	1006
Angle Shear 90degree (mm)	100 x 100 x 13
Angle Shear 45degree(mm)	80 x 80 x 8
Angle Flange Trim (mm)	100
Angle Shear Work Table Height (mm)	1236
Round Solid Bar Shear (mm)	40 diameter
Square Solid Bar Shear (mm)	38 x 38
Solid Bar Shear Work Table Height (mm)	1260
Notching rectangle (mm)	50.8 x 90 x 8
Notching Work Table Height (mm)	1006
Motor Power (kw/hp)	5.5/7.5
Voltage/Amperage (V/amp)	415
Shipping Dimensions (LxWxH)(cm)	146x77x166
Nett Weight (kg)	1600